

**Input**

Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Input Connections	IEC-320 C14

**Surge Protection and Filtering**

Surge energy rating	300 Joules
---------------------	------------

**Physical**

Maximum Height	116.00 mm
Maximum Width	214.00 mm
Maximum Depth	141.00 mm
Net Weight	3.10 KG
Shipping Weight	3.40 KG
Shipping Height	175.00 mm
Shipping Width	273.00 mm
Shipping Depth	207.00 mm
Master Carton Units	4.00
Master Carton Dimensions (Length 16.73 inches x Width x Height)	
Master Carton Weight	32.00 lbs.
Color	Beige
SCC Codes	1073130419789 5
Units per Pallet	64.00

**Environmental**

Operating Environment	0 - 40 °C
Operating Relative Humidity	5 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95%
Storage Elevation	0-15000 meters

**Conformance**

Regulatory Approvals	C-tick, CE, EN 55024, EN 60950, GOST, GS Mark
Standard Warranty	2 years repair or replace

**Sustainable Offer Status**

RoHS	Compliant
Other Environmental Compliance	China RoHS