



Specification	AS-360P-IP
Optoelectronic	
Lens	1/3" Fisheye lens, f=1.16mm, F=2.0
Field of Vision	Horizontal 182°/Vertical 166°
Iris	Fixed F2.0
Sensor	1/3.2" Progressive Scan CMOS
Sensibility	0.3Lux@F2.0(Color)/0.03Lux@F2.0(B/W)
Day/Night	Auto switch IR cut
IR Illumination	Omni-directional 3W@850nm, 10m effective distance
Image	
Image Flip	Horizontal/Vertical
Image Adjustment	Brightness, Saturation, Sharpness, Contrast, Tone
Max. Resolution	3.0 Megapixels (2048×1536)
Video Coding	Dual Stream H.264
Bit Rate	300Kbps~8192Kbps
Max. Frame Rate	20fps
Audio	
Microphone	Internal
Audio Coding	G.711
Pickup Distance	6 Meters
Audio Output	Internal speaker
Panoramic Function	Enabled by software
Panoramic Display	Support kinds of unwrap function based on ceiling, wall and floor mount; Support multiple virtual camera display
DPTZ	Digital PTZ, Pan/Tilt/Zoom
Intelligent Function	
Motion Detection	4×3Regional detecting, Sensibility 1~6 adjustable
Alarm Function	
Alarm Trigger	Motion Detection/Video Tampering/Abnormal procedure/Alarm Input/Storage Error/Storage Full/IP Conflict/Network Disconnection
Alarm Action	Alarm Record/Image Snap, Alarm Video/Image Upload (FTP/Email)
Network	
Protocol	TCP/IP, HTTP, DHCP, DNS, RTP/RTSP, FTP, PPPOE, SMTP, NTP
Compatibility	ONVIF2.0
WiFi(Optional)	IEEE802.11b/g/n
Interface	
Network Port	RJ45 10M/100M/1000M Ethernet
Alarm Input	1CH
Power Interface	ø5.5-2.1mm round DC socket
Local Storage	Up to 128G SD Card
Reset	One button reset
General	
Power Supply	DC12V±10%
POE(optional)	DC48V±10%
Power Consumption	<9W
Working condition	-15℃~+50℃@Humidity 10%~95%
Storage Condition	-40℃~+75℃@Humidity 10%~95%
EMC	CE, FCC

Housing	PC White
Protection Grade	IP50
Product Size	Φ148.5×57.5mm
Package	186×186×78mm
Weight (kg)	N.W.: 0.5 / G.W.: 0.65
Optional Function	-W: Wi-Fi、-P: POE

