

Model Number		AS-MS-01D
Scanning System	NTSC	525 lines 2:1 interlace
	PAL	625 lines 2:1 interlace
Scanning Frequency	NTSC	15,734Hz(H) , 60Hz(V)
	PAL	15,625Hz(H) , 50Hz(V)
Effective Pixel	NTSC	510(H) x 492(V)
	PAL	500(H) x 582(V)
Electronic Shutter	NTSC	1/60-100,000sec.
	PAL	1/50-100,000sec.
Image Device	1/3" SONY Super HAD CCD	
Horizontal Resolution	480 TV lines	
Sensitivity	0.01Lux	
Signal to Noise	More than 52dB	
Gain Control	Auto + 18dB Max	
White Balance	Auto 2500~9500oK	
BLC	Auto	
Gamma Correction	0.45	
SYNC System	Internal	
Lens/Focus point	6mm	
Video Output	1.0 Vp-p 75 Ohm	
Sense-UP times	Max 32 times	
Protection Class	IP 66	
Power Requirement ($\hat{A}\pm 10\%$)	DC12V, 500mA	
Power Consumption ($\hat{A}\pm 10\%$)	80mA	
Construction	Aluminium with sun-shield weatherproof	
Operating Temp.	Working: -10~+55oC, Storage: -30~+80oC, Humidity:0~95%RH	
Dimension(mm)	65(W) x 70(H) x 112(L)	
Weight(N.W)	0.37kg	