

AS-HDV-08 Specifications

Model no.	H8-04	H8-08	H8-16
Display & Audio			
Camera Input	4	8	16
Output	1 BNC/1 VGA/1 HDMI		
Audio input/output	4 RCA/1 RCA		
Sensor in/alarm out	4 (NC, NO selectable)/ 1 (Relay output)		
Operating System	Embedded Linux OS		
Display Speed	Real time		
Display Resolution	720 x 480 (NTSC, 720 x 576 (PAL)		
Display Split Screen	1,4 Sequence	1,4,6,8,9 Sequence	1,4,6,8,9,13,16 Sequence
Compression Format	H.264 (DSP)		
Picture Quality	4 LEVEL (Super, High, Medium, Low)		
Recording			
Recording Speed	CIF	120/100fps	120/100fps
	2CIF	120/100fps	240/200fps
	D1	120/100fps	240/200fps
Playback Display	1,4	1,4,8	1,4,8,16
Search Mode	Calendar, Event		
Playback Speed	Normal, REW & FF [Recorded Speed x2, x4, x8, x16, x32, x64, x1/2, x1/4] Frame to frame, Pause		
Connectivity			
Network Interface	Ethernet, DDNS		
Network Protocol	TCP/IP, HTTP, DHCP		
Application	Windows 2000/XP/Vista (PC Client Systems & IE)		
Web Browser	Internet Explorer		
Backup	Network, USB 2.0 Thumb Drive, DVD		
HDD	Supports 2 SATA HDDs		
HDD MIRROR	Support		
Specifications			
Display Rate	Real-time display		
Operating Temperature	5~40°C (41~104°F)		
Relative Humidity	Maximum 80% non-condensing		
Dimension (mm)	T1: 430mm (W) x 330mm (D) x 60mm (H) T2: 430mm (W) x 330mm (D) x 60mm (H)		
Weight (N.W)	Approx. 6.5kg (W/O HDD)		