

## AS-HDV-04F Specifications

MODEL NUMBER	AS-HDV-04	
Camera Input	4	
Video Output	1 BNC 1 VGA, selectable	
Audio Input / Output	4 RCA/ 1 RCA	
Sensor In/ Alarm out	1(NC, NO selectable)/ 1(Relay Output)	
Operating System	Embedded Linux OS	
Display Speed	Real Time	
Display Resolution	720 x 480(NTSC), 720 x 576(PAL)	
Display Split Screen	1,4 Sequence	
Compression Format	H.264 (DSP)	
Picture quality	4 Levels (Super, High, Medium, Low)	
Recording Speed	NTSC	CIF: 120 FPS Half D1: 60FPS + 3FPS(CIF) D1: 25FPS + 3FPS(CIF)
	PAL	CIF: 100 FPS Half D1: 50FPS + 3FPS(CIF) D1: 25FPS + 3FPS(CIF)
Playback Display	1,4	
Search Mode	Calander, Event	
Playback Speed	Normal, REW & FF [recorded speed x2, x4, x8, x16,x32,x64,x1/2,x1/4],Frame to frame, Pause	
Network Interface	Ethernet, PPPoE	
Network Protocol	TCP/IP, HTTP, DHCP	
Application	Windows 7 / 2000 / XP / Vista (PC Client Systems & IE)	
Mobile Application	Support 3G Mobile Phone Viewing (iPhone, Blackberry, Android, Windows Mobile, JAVA, Symbian OS)	
Web Browser	Internet Explorer	
Backup	Network, USB 2.0	
HDD	Supports 1 SATA HDD	
Power Consumption	12V / 3.3A	
Operating Temperature	5 ~40° C(41~104° F)	
Relative Humidity	Maximum 80% non-condensing	
Dimensions(mm)	337(W) x 256(D) x 60(H)	
Weight(N.W)	Approx. 1.8kgs ( W/O HDD)	