


Specification: AS-700VF



Model No.	AS-700VF
Image Sensor	1/3" Sony 650TVL (ICX811AK+CXD4140GG)
Scanning System	2:1 Interlace
Total Pixel	PAL:960H*582V NTSC:967H*494V
Horizontal Resolution	650TVL
Min. Illumination	0.03Lux@F1.2, 0Lux (IR ON)
S/N Ratio	≥52dB
Video Output	CVBS:1.0Vp-p/75Ω Composite
Gamma Correction	0.45
Frequency	H:15.734 KHz/V:15.625KHz/V:50Hz
Sync. System	Internal Synchronization
<u>Day&Night</u>	Auto/ Color/ B/W
Shutter Speed	1/50 -1/10,000 SEC
Scanning System	2:1 Interlace
White Balance	ATW/PUSH/USER1/USER2/ANTI CR /MANUAL/PUSH LOCK
BLC	OFF/BLC/HLC
Mirror	Flip Horizontal
Motion Detection	8 Area Setting
Privacy	8 Area Setting
A.G.C	Auto/Manual
On Screen Display	Chinese,English,French,German,Russian,Japanese,Spanish,Portuguese
Sharpness	On/Off (Level Adjustable)
ATR	On/Off
Noise Reduction	2D-DNR
Power Supply	DC12V±5%
Power Consumption	≤6W
Humidity	≤85%RH
Operation Temp.	-10°C~+50°C
IR Led	48pcs Φ 5 IR LED, 40m IR range
Lens Type	2.8-12/4-9mm Fixed Iris <u>Vari</u> -focal Lens
Dimensions	186mm x 85mm x 128mm
Weight	0.7kg