

AS-HDMI MIDI EX Specifications

Product Model	FS-HD2001E (TX)	FS-HD2001E (RX)
Input port	HDMI Connector Type A 19 pin Female	2*RJ-45 Female
Output port	2* RJ-45 Female	HDMI Connector Type A 19 pin Female
LED Indicator	Red: power	Red: power
	Yellow: Remote control sends signal	Yellow : Remote control receives signal
	Green: HDMI activity	Green: HDMI activity
Protection	Lightning Protection	15KV IEC61000-4-5 1995(GB/T 17626.5) 1000V, 10/700us IEC61000-4-5 1995(GB/T 17626.5)
	Anti-static Protection	Contact Discharge:+-8KV Air Discharge:15KV IEC6100-4-5 1995(GB/T 17626.5)IEC61000-4-2
Signal input/output	Video input	0.5 -1.0 volts p-p
	Video output	1.0 volts p-p
	Max transmission speed rate	10.2Gbps
	Input DDC signal	5 volts p-p (TTL)
	HDMI Max input/output	1920X1200, 1080P and 36 digits colorific 1080p HDTV resolution 1920X1200, 1080P and 366 digit colorific 1080p HDTV resolution
Video Format	HDMI input/output	24/50/60fs/1080p/1080i/720p/576p/576i/480p/480i
Support HDTV	Interlaced Scanning (50&60Hz)	480i,576i,1080i
	progressive-scan(50&60Hz)	480p,576p,720p,1080p
	PC	VGA、SVGA、XGA、SXGA、UXGA and WUXGA
Transmission Distance		100m (480p) via UTP cat5e/6 40m(1080p) via UTP cat5e/6
Power Supply	Power Adaptor	90V-250V/AC input, 50/60Hz; 5VDC output; 500mA ,
	Operating Current	400mA(Max)
	Power consumption	2Watts (Max)
Mechanical	Housing	Galvanized
	Body Color	Black
	Dimensions(L*W*H)	91*61.5*23.5cm
	Net Weight	200g
Environmental	Operating Temperature	0°C to +70°C
	Relative Humidity	0~95% (non-condensing)
	Storage Temperature	-40° ~ 150° C