


Model number		AS-NVR1080P-IP
Image		
Chipset		Hi3520D
RAM		256MB DDR3
OS		Embedded Linux
Video&Audio input	IPC Input	48Mbps
		8CH
Video&Audio output	CVBS	1CH,BNC (1.0Vp-p,75ohms)
	VGA	1CH,Resolution 1920x1080,1280x1024,1280x720
	HDMI	Standard 1.3a
		Resolution 1920x1080,1280x1024,1280x720
Audio Output	1CH,RCA(Line out,2Vpp,300ohm)	
Video&Audio encoding	Audio Compression	G.711A
	Audio Bit Rate	64Kbps
Video&Audio decoding	IP Resolution	Main stream:up to 1920x2048 Auxiliary stream:D1
	Video bitrate	Up to 2Mbps@D1,4Mbps@720P,8Mbps@1080P
	Video decoding	MPEG-4/H.264(Up to High Profile@Level 4)
	Synchronous Playback	Up to 8CH
	Decoding Ability	Up to 4CH 720P@30 or 2CH 1080P@30
Other Function	Bidirectional Talk	N/A
	Motion Detection	Zones: 396(22x18), Sensitivity: 1~6 (level 1~6)
	Picture Capture	Local Capture&Web Capture
HDD Interface	SATA	2
	Max Capacity	no limited
External Interface	Network Interface	1 RJ45 10M/100M adaptive Ethernet interface
	USB	2 USB 2.0 Interfaces
	Alarm Input	4CH
	Alarm Output	1CH
	RS-485	1 RS-485 interface
Size&Weight	Dimensions	405x335x120mm
	Front Panel	LED
	Size	360x260x48mm
	Weight	2Kg(without HDD)
General	Power Supply	DC +12V 4A
	Working Temperature	-10℃--+55℃
	Working Humidity	10%--90%

	Consumption	5W(without HDD)
--	-------------	-----------------

