

AS-G15BAL**Spec**

MODEL NUMBER	AS-G15BAL
Image Pick-up Device	SONY 1/3" Super HAD CCD
Total Pixels	NTSC: 537(H) x 505(V) / PAL: 537(H) x 597(V)
Effective Pixels	NTSC: 510(H) x 492(V) / PAL: 500(H) x 582(V)
Horizontal Resolution	420TVL
Sync system	Internal
Scanning System	2:1 interlace
S/N Ratio	More than 48dB (AGC OFF)
Electronic Shutter	Auto 1/60(1/50) ~ 1/100,000 sec.
Min. Illumination	0.1 lux / F2.0(50IRE)
Video Output	1.0V p-p composite video at 75 ohm
IR Distance	15M(18pcs IR LED)
IR Trigger	2.6 lux/2.7 lux IR ON/OFF
Auto White Balance	2400° K ~ 9400° K
Gamma Correction	0.45
Lens	Board Lens 4.3mm
Power Source	DC12±10%(1A)
Power Consumption	2.88W
Current	240mA(Max)
Operation Temperature	-10° C ~ + 50° C(14°F ~ 122°F)
Storage Temperature	-20° C ~ + 70° C(-4°F ~ 158°F)
Dimension	70(H) x 94(Diameter)
Weight	N.W./G.W.: 0.32kg/0.38kg
Weatherproof	IP66